

DILLON®

Mechanical AP Dynamometers



Installation Instructions

Dillon is part of Avery Weigh-Tronix. Avery Weigh-Tronix is a trademark of the Illinois Tool Works group of companies whose ultimate parent company is Illinois Tool Works Inc ("Illinois Tool Works"). Copyright © 2017 Illinois Tool Works. All rights reserved.

No part of this publication may be reproduced by making a facsimile copy, by the making of a copy in three dimensions of a two-dimensional work and the making of a copy in two dimensions of a three-dimensional work, stored in any medium by electronic means, or transmitted in any form or by any means, including electronic, mechanical, broadcasting, recording or otherwise without the prior written consent of the copyright owner, under license, or as permitted by law.

This publication was correct at the time of going to print, however Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.

Table of Contents

	<i>page</i>
Chapter 1 General information and warnings	3
About this manual	3
Text conventions	3
Special messages	3
Safe operation	4
Routine maintenance	5
1.5 Cleaning the Dynamometer	5
Training	5
Declaration of conformity	6
Chapter 2 Introduction	8
General description	8
Third-party shackles and attachments	10
Maintenance and handling	10
Chapter 3 Operation	11

1 General information and warnings

1.1 About this manual

This manual is divided into chapters by the chapter number and the large text at the top of a page. Subsections are labeled as shown by the 1.1 and 1.1.1 headings. The names of the chapter and the next subsection level appear at the top of alternating pages of the manual to remind you of where you are in the manual. The manual name and page numbers appear at the bottom of the pages.

1.1.1 Text conventions

Key names are shown in bold and reflect the case of the key being described. If a key has a dual function it may be referred to by its alternate function.

Displayed messages appear in bold italic type and reflect the case of the displayed message.

Annunciator names appear as italic text and reflect the case of the annunciator.

1.2 Special messages

Examples of special messages you will see in this manual are defined below. The signal words have specific meanings to alert you to additional information or the relative level of hazard.



WARNING! This is a Warning symbol. Warnings mean that failure to follow specific practices and procedures may have major consequences such as injury or death.



CAUTION! This is a Caution symbol. Cautions give information about procedures that, if not observed, could result in damage to equipment or corruption to and loss of data.



NOTE: This is a Note symbol. Notes give additional and important information, hints and tips that help you to use your product.

1.3 Safe operation



WARNING: If you overload this dynamometer you could suffer severe injuries or death. The total load on the dynamometer should NEVER exceed the rated capacity.

Keep all the following in mind as you use the dynamometer.

The system capacity is equal to the rating of the dynamometers. The shackle rating should not be used to determine lift capacity of the system.

The shackles are rated in metric tonnes. Thus the 12-tonne shackles are rated to 26,450 lbf and are suitable for use on the 25,000 lbf dynamometer.

Any zeroed deadload must be considered as part of the ultimate load.

Although this instrument has a substantial overload protection rating, the instrument should not be used above the rated capacity. Doing so can significantly impact fatigue life of the instrument and cause premature and abrupt failure. If a higher capacity reading is needed, Dillon insists that a larger instrument be used.

Safety is always a concern in overhead lifting and tensioning applications. To limit your liability always insist upon factory supplied shackles and pins and factory tested and certified safe optional equipment. All DILLON products are designed to meet the published Safe Working Load (SWL) and Ultimate Safety Factor (USF) standards of the United States Military. All CE marked models meet the SWL and ULL (Ultimate Load Limit) requirements of the European Machinery Directive.

Do not grind, stamp, drill or deform the metal on the dynamometer body in any way. Protect the instrument from impact in use and storage.

Any significant damage or deformation to the loading element is cause for evaluation by Dillon.

Relieve all torsional and off axis loads.

Apply load in the center of the shackle bow with this instrument.

Off center loading results in substandard performance.

Instrument requires time to stabilize when changing temperatures.

Use only the hardware supplied with this instrument. If no hardware was supplied, insure that the mating pin and shackle bow is equivalent to the hardware used at calibration. Otherwise substandard performance or failure can result.

Dillon recommends only using qualified rigging hardware and cannot be responsible for unapproved hardware.

This instrument is not designed for the following:

- Applications that see rapid, dramatic temperature swings or thermal shock. Wide variation in readings can occur.
- Intrinsically safe environments. This unit has not been Factory Mutual or ATEX tested.

1.4 Routine maintenance



IMPORTANT: This equipment must be routinely checked for proper operation and calibration.

Application and usage will determine the frequency of calibration required for safe operation.

1.5 Cleaning the Dynamometer

Cleaning DOs and DON'Ts

- DO - Wipe down the outside of standard products with a clean cloth, moistened with water and a small amount of mild detergent
- DO NOT - Attempt to clean the inside of the machine
- DO NOT - Use harsh abrasives, solvents, scouring cleaners or alkaline cleaning solutions

1.6 Training

Do not attempt to operate or complete any procedure on a machine unless you have received the appropriate training or read the instructions.

1.7 Declaration of conformity



ES	Declaración UE de Conformidad	Dillon AP
Modelo / Tipo: Dillon AP		
Número de la Serie: Aparato del X1250		
<p>Nombramiento y dirección del destinatario Avery Weigh-Tronix 1000 Technology Lane Suite 100 West Milwaukee WI 53219-3747 U.S.A.</p>		
		
<p>Objetivo de la declaración: Se declara que el dispositivo mencionado se encuentra dentro de los límites de rendimiento establecidos en la especificación técnica correspondiente.</p> <p>Objetivo de la certificación: Se declara que el dispositivo mencionado cumple con las normas y especificaciones técnicas establecidas en la especificación técnica correspondiente.</p> <p>Objetivo de la autorización: Se declara que el dispositivo mencionado cumple con las normas y especificaciones técnicas establecidas en la especificación técnica correspondiente.</p>		
<p>La información incluida en esta declaración es pertinente para el dispositivo mencionado y se ha verificado que es correcta.</p> <p>El destinatario de la declaración, descrita anteriormente es: Avery Weigh-Tronix, Inc., una empresa que opera de acuerdo con las leyes y regulaciones de la Unión Europea.</p> <p>Directrices específicas: Normas y especificaciones técnicas.</p>		
<p>Información adicional:</p> <p>Nota: La fundación Avery Weigh-Tronix, Inc. (TVA) ha quedado en Avery Weigh-Tronix, Inc. Oficina registrada Natura House, Station Road, Egham, Surrey, KT14 7BL, Reino Unido.</p> <p>Nota: Avery Weigh-Tronix, Inc. es un socio del expediente técnico Mensor correspondiente a este equipo en la dirección que se indica.</p>		
<p>Firmante en nombre de: Avery Weigh-Tronix en: 1000 Armstrong Drive, Farmington, MN, 56063-1449, EE.UU. el: _____ Firma: _____</p> <p>2017-07-18</p> <p>K. K. Hart Innovaciones / Director de Marketing</p>		

76501-504 Issue 2

NL EU - Conformiteitsverklaring	Model / Type: Dillon AP Surgeon's Timer, Variof X1250	
<p>Naam en adres van de verkoper : Avery Weigh-Tronix 10000 Technology Lane Sparta, WI 54601-1000 USA</p> <p>Naam en adres van de fabrikant : Avery Weigh-Tronix West Milwaukees Bld. 21 P ENGELAND</p>		
<p>Dit model telt een volledig aantal verschillende mogelijkheden voor verschillende toepassingen van de Richtlijn en moet daarom de volgende beschrijvingen van de toepassing van de richtlijn.</p> <p>Het hierboven beschreven concurrerende is in overeenstemming met de richtlijnen en de voorwaarden van de Unie.</p> <p>Kopieën van deze verklaring kunnen alleen worden aangevraagd bij de fabrikant.</p> <p>Gedownloaden kopieën zijn niet geldig.</p> <p>Deze verklaring is alleen van toepassing op de volgende technische specificaties:</p>		
<p>Voorbeeld van de verklaring:</p> <p>Dillon[®] 19.5 g - 500g - 20.000g Dillon[®] AP - 19.5 g - 500g - 10.000g Dillon[®] AP V - 19.5 g - 500g - 20.000g Dillon[®] AP V - 19.5 g - 500g - 20.000g</p>		
<p>Aanvullende informatie:</p> <p>Noot 1: TIV Ltd trading als Avery Weigh-Tronix Zetel: News House, Station Road, Egrem, Surrey KT20 2BL, Engeland</p> <p>Noot 2: Dillon is een onderdeel van Avery Weigh-Tronix Een deel van het technisch bestand voor deze apparatuur is verkregen van M.S. Williams op het bovenstaande adres.</p>		
<p>Onderkendend voor een namens: Avery Weigh-Tronix</p> <p>In:  100 1000 Technology Drive, Farmington, MN 55033-1439, Op: 2017-07-18 KGD/Marketing Director / Marketing Director</p>		

DE	Konformitätserklärung
Modell / Typen: Dillon AP	
Sortimentsnummer: AX1250	
Name und Anschrift des Herstellers: Avery Weigh-Tronix Avery Technology Line 5000 E. Mineral Ave. Suite 100 West Allis, WI 53219-2810 P ENGLAND	
Gesamtgewicht der Prüfungseinheit : 10 kg Gewichtsmaßstab der Prüfungseinheit : 5 kg bis 10 kg Präzision : 10g Daten : DP, 12, 14, 16, 18, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56, 60, 64, 68, 72, 76, 80, 84, 88, 92, 96, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 148, 152, 156, 160, 164, 168, 172, 176, 180, 184, 188, 192, 196, 200, 204, 208, 212, 216, 220, 224, 228, 232, 236, 240, 244, 248, 252, 256, 260, 264, 268, 272, 276, 280, 284, 288, 292, 296, 200000g	
Dieselbe Maschine dient für alle überliegenden Bedienungsanweisungen der Anwendung nach DIN EN 60642-100	
Der oben beschriebene Gegenstand erfüllt die Anforderungen an die einschlägigen Normen und Richtlinien der Union Angewandte Richtlinie: Normen sowie sonstigen technischen Spezifikationen	
Zustimmung: Anmerkung: TÜV ist ein Handelsname von Weigh-Tronix 522 New House, Shire Vale, Egham, Surrey, TW20 9LJ, England Anmerkung: TÜV ist ein Teil von Avery Weigh-Tronix Anmerkung: Eine Kopie dieses Dokuments ist bei dem Unternehmen für dieses Gerät aufzufinden unter der vorstehenden Adresse	
Unterzeichnet für und im Namen von: John 6000 Marketing Drive, Farmington, MN, 56031-1439, USA	
10.07.18	
KLJedet	

EN	EU Declaration of Conformity
Model / Type: Dillon AP	
Serial Number: X2180 Onwards	
Name and address of the manufacturer: Avery Weigh-Tronix 1000 W. 7th Street West Allis Milwaukee WI 53210 U.S.A.	
 <p>The machine(s) falling within the meaning of the term "machinery" as defined in Directive 2006/42/EC</p>	
<p>The object of the declaration is in conformity with the relevant Union harmonized standard referred to in Article 10(1) of Directive 2006/42/EC or other technical specifications</p>	
<p>The following statement is made in accordance with Article 12(2)(a) of Directive 2006/42/EC:</p> <p>I, M. S. Williams, declare under my sole responsibility that the equipment described above is issued under the sole responsibility of the manufacturer.</p> <p>Object of the Declaration:</p> <p>P 1500-2000kg P 2500-3000kg P 3500-4000kg P 4000-4500kg P 4500-5000kg P 5000-5500kg</p> <p>Applicable Directives:</p> <p>Applicable harmonized standard(s) referred to in Article 10(1) of Directive 2006/42/EC</p>	
<p>Additional information:</p> <p>Note 1: Trading as Avery Weigh-Tronix Reg. Office: Naval House, Salter Road, Eggbrook, Surrey, GU20 1BZ, England</p> <p>Note 2: Trading as Avery Weigh-Tronix Dillon is part of Avery Weigh-Tronix.</p> <p>Note 3: A copy of the Technical File for this equipment is available from M. S. Williams at the address above.</p>	
<p>Signed for and on behalf of: Avery Weigh-Tronix M. S. Williams, Marketing Director</p> <p>Signature of M. S. Williams</p>	
<p>Date: 2017-07-18</p>	

The 50,000 lb dynamometer is not CE approved.



UK Declaration of Conformity	
Model / Type: Dillon AP	
Serial Number: X12500 Onwards	
Name and address of the manufacturer: Avery Weigh-Tronix ¹ Foundry Lane Smetwick West Midlands B66 2LP ENGLAND	
This declaration of conformity is issued under the sole responsibility of the manufacturer	
Object of the declaration: Dillon ⁴ AP 5' 500lb - 20,000lb Dillon ⁴ AP 5' 500kg - 10,000kg Dillon ³ AP 10' 1000lb - 30,000lb Dillon ⁴ AP 10' 500kg - 20,000kg	
	
The machinery fulfills all the relevant provisions of the Machinery Directive 2006/42/EC ³	
The object of the declaration described above is in conformity with the relevant statutory requirements applicable to the specific product:	
Statutory Requirements	UK standards or other technical specifications
Additional information: Note 1: ITW Ltd trading as Avery Weigh-Tronix Reg. Office: Nexus House, Station Road, Egham, Surrey, TW20 9LB, England Note 2: Dillon is part of Avery Weigh-Tronix Note 3: A copy of the Technical File for this equipment is available from M.S. Williams at the address above.	
Signed for and on behalf of: Avery Weigh-Tronix at 1000 Armstrong Drive, Fairmont, MN, 56031-1439, USA on 2021-07-16	
 E. Holland Director - R&D and Innovation	

76501-504UK Issue 1

2 Introduction

2.1 General description

A dynamometer is an instrument that displays the tension force exerted between the two attached shackles. It is generally used to determine tension in a line/cable or for suspended weighing.



The 50,000 lb dynamometer is not CE approved.

Figure 2.1 shows one model of dynamometer.




Figure 2.1 Dynamometer with shackles



CAUTION: Dillon Dynamometers are not designed for measurement of dynamic shock loads and should not be subjected to sudden force. Load or weight should be applied in a gradual manner to avoid damaging the Dynamometer. Torque loads applied to the dynamometer should be relieved or avoided.

Heavy duty needle bearings inserted in each end of the Dynamometer deflection beam (or into both sides of the shackles ears) allow the shackle pin to rotate as force is applied. See [Figure 2.1](#). Bearings should be cleaned periodically in a suitable solvent. After drying, the bearings should be treated with a coat of light machine oil (SAE-5W non-detergent oil or lighter).



CAUTION: DO NOT allow oil to run into the mechanism case. The mechanism should never be oiled as this tends to attract dust or dirt.

The case is not water-tight and if the Dynamometer should be accidentally immersed, hold it so that water is free to run out through the openings in the bottom of the case and allow to dry.

2.2 Third-party shackles and attachments

Dillon supplies shackles and pins with the dynamometers that have been confirmed to properly work with our mechanical dynamometers. Do not use shackles or shackle pins that have not been qualified by Dillon. Lower profile non-machined spots can often be observed and are normal.

If any type of accessory fitting is made for use with the Dillon Dynamometer, be sure to machine this from high grade aircraft alloy (E4340 steel or equivalent) and heat treat it in order to ensure maximum safety.



Dillon / Avery Weigh-Tronix is not responsible for failure of attachment fittings furnished by others.

2.3 Maintenance and handling

The Dillon Dynamometer is a precision instrument and will provide many years of dependable service if given reasonable care and suitable protection. Many firms make it a regular practice to return Dynamometers to their distributors at 6 to 8 month intervals (depending upon how much they are used) to have accuracy recertified. We recommend this at least once a year. Consult with your Dillon distributor concerning any questions you may have about recalibration intervals. Your area may require periodic proof testing. Consult your local regulations.

Transport and store the dynamometer in the supplied storage case when not in use.

3 Operation

Zero the dynamometer for best accuracy. To properly zero the instrument when using the max pointer, adjust the black needle below the desired zero point using the zero adjustment wheel on the rear of the case. Move the red maximum pointer counterclockwise until it contacts the black needle. Use the zero adjustment wheel to simultaneously move both pointers to the desired zero point. This procedure will prevent the slight drag of the max pointer from influencing the displayed reading. If the max pointer is not required, rotate the red pointer clockwise until it reaches the zero position and operate normally.



WARNING: Failure to adjust the max hand prior to use of the Dynamometer WILL affect the readings if the max hand is used.

Dillon Mechanical Dynamometers permit zeroing of up to 20% of instrument capacity.
Do not zero off a deadload and then use the instrument to capacity.

DILLON®

AUTHORIZED DISTRIBUTOR

Dillon/Quality Plus, Inc.

Sales/Service/Calibration

214 E. Kansas Street Suite

101 Liberty, MO. 64068

Phone: 800-493-2263

Fax: 816-453-7677

Email: sales@dqplus.com

www.dillondynamometers.com

